

# Request for Quotation for Provision of IT equipment for the Superior Council of Magistracy

2003-RFQ-2024/0005

**April 8, 2024** 

Dexis Interactive Incorporated, Washington, Chisinau Branch of Dexis Consulting Group

8/1 Calea lesilor str., of 9A,

Chisinau, Republic of Moldova, MD-2069



# SUBJECT: REQUEST FOR QUOTATIONS FOR PROVISION OF IT EQUIPMENT FOR THE SUPERIOR COUNCIL OF MAGISTRACY

Dexis invites your firm to participate in this competitive solicitation for pricing, delivery, and terms of potential sale of IT equipment (videoconferencing equipment, server/NAS and UPS equipment) for the Superior Council of Magistracy. Dexis reserves the right to reject any and all offers, to add, delete, or modify any element of the solicitation at any time without prior notification and without any liability or obligation of any kind. This RFQ does not oblige Dexis to enter into a contract nor does it oblige Dexis to pay any costs incurred in the preparation of submission of any Response.

Dexis anticipates that this Request for Quotation (RFQ) will result in a **Purchase Order** (agreement) for the provision of IT equipment (videoconferencing equipment, server/NAS and UPS equipment) for the Superior Council of Magistracy.

#### **BACKGROUND**

Dexis Consulting Group is a for-profit company founded in 2001 to strengthen management systems for the U.S. Government across developing economies. Dexis provides monitoring and evaluation, program management, institutional support, project implementation, and training solutions to address some of the world's greatest challenges.

Dexis is currently implementing multiple US government funded projects in the Republic of Moldova, among which are the USAID-funded Model Court Initiative in Moldova (MCI) and Moldova Justice and Anti-Corruption Reform Activity (JARA). Our Moldovan projects focus on rule of law, justice sector reform and anti-corruption activities to support Moldovan citizens access to justice, improve services and the institutional capacity of justice sector agencies to serve all citizens.

In carrying out their activities, the projects collaborate with key actors and stakeholders in the Moldovan justice system, primarily the Superior Council of Magistracy (SCM), the Ministry of Justice (MOJ), the Agency for Court Administration (ACA), as well as courts throughout the country. The Projects' activities are led by a team of experienced national legal and IT experts with in-depth knowledge of the Moldovan judicial system.

# **DESCRIPTION OF GOODS/SERVICES**

With this RFQ, Dexis is soliciting offers from qualified companies for delivery of IT equipment for the Superior Council of Magistracy, as part of projects activities, in accordance with the specifications set forth below.

#### **TECHNICAL REQUIREMENTS**

The required goods (equipment) are structured into two lots. The local company(ies) are invited to submit their quotations for IT equipment under one, or both 'Lots' described below:

#### Lot 1 – Videoconferencing equipment

Item	Minimal Technical Specifications	Quantity
1	Central unit for conference system	
	·	Quantity
	Warranty Min. 36 months	
2	Chairman unit	

Item	Minimal Technical Specifications	Quantity
	Compatible with the central unit of the conference system.  Desktop type unit (on the table) equipped with a gooseneck type microphone of min. 60cm, with cardioid directional microphone capsule with windshield, with LED indicator - min. two colors (on, off).  OLED display, 128x32 mm, to show: sound level, clock, active unit time, microphone status (off/on)  Connection type: min. 2x RJ45 connectors for daisy-chaining multiple units via CAT5e cable  Touch buttons (min. 8): microphone ON/OFF, speech priority, application, five buttons for the voting function.  Audio output type 3.5mm stereo headphone connector.  Function to listen to the simultaneous translation signal through the unit's audio outputs. In this case, the buttons used for voting can also be used to choose the translation channel, as well as to adjust the volume in the headphones.  Audio sampling rate: 48 kHz  Minimum frequency range - 20Hz~20KHz  Sensitivity: -46 dBV /P  Microphone directivity: 0 ° / 180 °> 20 dB (1 kHz)  Anti-RF interference from mobile phone or similar devices  Automatic Gain Control / Adaptive Feedback Cancellation / Active Noise Control / Auto- Mix  Card reader with IC built into the unit housing. The set will include at least three IC cards.	1
3	Warranty Min. 36 months	
3	Delegate unit (Type 1)  Compatible with the central unit of the conference system.  Desktop type unit (on the table) equipped with a gooseneck type microphone of min. 60cm, with cardioid directional microphone capsule with windshield, with LED indicator - min. two colors (on, off).  OLED display, 128x32 mm, to show: sound level, clock, active unit time, microphone status (off/on)  Connection type: min. 2x RJ45 connectors for daisy-chaining multiple units via CAT5e cable  Touch buttons (min. 6): microphone ON/OFF, five buttons for the voting function.  Audio output type 3.5mm stereo headphone connector.  Function to listen to the simultaneous translation signal through the unit's audio outputs. In this case, the buttons used for voting can also be used to choose the translation channel, as well as to adjust the volume in the headphones.  Audio sampling rate: 48 kHz  Minimum frequency range - 20Hz~20KHz  Sensitivity: -46 dBV /P  Microphone directivity: 0 ° / 180 °> 20 dB (1 kHz)  Anti-RF interference from mobile phone or similar devices  Automatic Gain Control / Adaptive Feedback Cancellation / Active Noise Control / Auto- Mix	11

Item	Minimal Technical Specifications	Quantity
	Card reader with IC built into the unit housing. The set will include at least three	
	IC cards.	
4	Warranty Min. 36 months  Delegate unit (Type 2)	
-	Compatible with the central unit of the conference system.	2
	Unit built into the table equipped with a gooseneck type microphone of min. 60cm, with cardioid directional microphone capsule with windshield, with LED indicator - min. two colors (on, off). Touch button (1): microphone ON/OFF. Audio output type 3.5mm stereo headphone connector.  "Zero Latency" signal transmission and digital signal processing with protection against mobile phone interference.  Connection type: min. 2x RJ45 connectors for daisy-chaining via CAT5e wire Audio sampling rate: 48 kHz  Minimum frequency range 20Hz~20KHz  Sensitivity: -46 dBV/P  Automatic Gain Control / Adaptive Feedback Cancellation / Active Noise Control / Auto-Mix	-
	It must realize the automatic tracking function (preset) of the camera Warranty Min. 36 months	
5	Delegate unit (Type 3)	
	Compatible with the central unit of the conference system.  Desktop type unit (on the table) equipped with a gooseneck type microphone of min. 48cm, with cardioid directional microphone capsule with windshield, with LED indicator - min. two colors (on, off).  OLED display, 128x32 mm, to show: sound level, clock, active unit time, translation channels (for 2 people, with the possibility of separate selection), microphone status (ON/OFF)  Connection type: min. 2x RJ45 connectors for daisy-chaining multiple units via CAT5e cable  Touch buttons (5): microphone connection/disconnection, two sets of two translation channel selection buttons for each of 2 users and to adjust the volume in the headphones.  Audio output: 2*3.5mm stereo headphone jack for each participant (2)  Audio sampling rate: 48 kHz  Minimum frequency range - 20Hz~20KHz  Sensitivity: -46 dBV /P  Microphone directivity: 0 ° / 180 °> 20 dB (1 kHz)  "Zero Latency" signal transmission and digital signal processing with protection against mobile phone interference.  Automatic Gain Control / Adaptive Feedback Cancellation / Active Noise Control / Auto-Mix  Warranty Min. 36 months	3
6	Software module for voting procedure	
	Software module for voting procedure, compatible with the central conference unit  Management of different types of voting (anonymous/nominal)	1

Item	Minimal Technical Specifications	Quantity
	Real-time viewing of voting procedure progress on screen/display/projector/TV	
	Function to import and export *.xls documents	
7	Software module for integrated circuit (IC) card management	
	Software module for IC card management.	1
	Function to choose authentication type: using the physical card or the nominal	
	set-up of each unit.	
	Programming with detailed personal information of cards and/or units.	
	Functions for reading information from the IC card; recording in the software the	
	loss of the card, as well as deleting the information on the card.	
	Function to import and export *.xls documents.	
8	IC card programming unit	
	Hardware module for programming IC cards, which connects to the computer via	1
	USB port.	
	Functions: connection with the software module for managing IC cards, writing	
	and reading encrypted information on IC cards (name, surname etc.).	
9	Sound Amplifier	
	Output power – min. 120 W	1
	Inputs:	
	3 x balanced XLR	
	3 x stereo RCA	
	6 x 6.3mm jack connector	
	1 x 3.5mm TRS Jack.	
	Outputs: 6 x phoenix	
	2 x 6.3mm Jack	
	Minimum frequency range: min. 80 Hz - 15 kHz	
	THD – 0.5% at 1kHz power	
	Equalizer - 125 Hz, 250 Hz, 500 Hz, 1 kHz, 2 kHz, 4 kHz, 8 kHz, ± 12 dB	
	Phantom power – min. 15V	
	Possibility to divide the output signal into at least 5 zones	
	Can be installed on a table or rackmounted	
	Possibility to connect 40hm / 25V / 70V / 100V speakers	
	Possibility to adjust the volume of the inputs and master	
	Warranty Min. 24 months	
10	Speaker	
	Type: with casing	4
	Nominal power: min.20 W (8 Ω)	
	Power transformer: min. 20W - 10 W - 5 W - 2.5 W - 8 Ω	
	Sensitivity: min.89 dB (1 W/1 m)	
	Frequency range: min. 90 Hz – 20 kHz	
	Weight: max. 2.5 Kg	
	Material: Polypropylene housing with aluminum grid	
	Steel U-bracket for wall mounting	
	Warranty Min. 24 months	
11	Wireless microphone system	

Item	Minimal Technical Specifications	Quantity
	Wireless system with two dynamic cardioid hand microphones with frequency	1
	selection (min.32). Included in the package: wireless receiver + two antennas +	
	19" (1U) rack mount, two transmitters, power supply unit, unbalanced jack-jack	
	cable.	
	Minimum specifications for the receiver:	
	Power supply 12-15V DC, 1.25A	
	Outputs: 2x XLR balanced, 1 x 6.3 mm TS JACK unbalanced	
	Operating frequency range: min. 606 MHz - 621 MHz	
	Sensitivity: 6 dB μV	
	THD: <0.7%@1KHz	
	Control: On/Off, Gain	
	Outputs: 2 x XLR balanced, 1 x Jack 6.3mm unbalanced	
	Minimum specifications for transmitters:	
	Power supply – 2*AA 1.5V batteries (non-chargable)	
	Type – handheld	
	Frequency range: min. 45 Hz - 18 kHz	
	Built-in spiral antenna	
	Signal to noise ratio: > 105dB	
	Warranty Min. 24 months	
12	Feedback suppressor	
	Fully automatic adaptive algorithm.	1
	Must support at least 4*XLR inputs (line/mic), 1*RJ45 audio input, 1* RCA audio	
	input, 1* RCA audio output, 1* XLR audio output.	
	Maximum input level – at least 6dBv	
	Output resistance - <100 ohm	
	min. 24V phantom power (microphone only, switchable)	
	Warranty Min. 36 months	
13	Digital signal processor (DSP)	
	DSP platform for microphone and line level audio processing. Processor	1
	configuration can be done in real time with a computer via USB	
	Power consumption: max. 12W	
	Inputs – min. 4 x Balanced Phoenix	
	Outputs – 6 x Balanced Phoenix	
	Input impedance: 4.7 kOhm	
	Output impedance: 100 Ohm	
	Maximum output level:+10dBu	
	Maximum gain: -28dBu	
	Frequency response: 20 Hz- 20kHz	
	Distortion: 0.01% @ 1 kHz	
	Sampling rate: 48 kHz	
	AD/DA converters: 24 bit, 48 kHz sample rate	
	Warranty Min. 24 months	
14	Conference camera	<u> </u>
	Motorized camera, with the possibility of rotation, must be from the same	4
	manufacturer as the conference microphone system in order to be able to	
	I manaratarer as the comercine interophone system in order to be able to	<u> </u>

Item	Minimal Technical Specifications	Quantity
	automate the position and zoom according to each microphone in the system.	
	Wall mounting bracket included.	
	Native resolution min. 1080P Full HD	
	Connection to PC via USB3.0 cable for using ZOOM, Skype, Teams, etc. software	
	USB Video Communication Protocol - UVC 1.0	
	Sensor: 1/2.8", CMOS, Effective Pixel: 2.07M	
	Lens: 20x optical zoom, f4.42mm ~ 88.5mm, F1.8 ~ F2.8	
	Color System: YUV 4:2:2/MJPEG/H.264	
	Video format: USB3.0: 1080p/60, 1080p/50, 1080p/30, 1080p/25, 720p/60,	
	720p/50, 720p/30, 720p/25	
	Horizontal rotation range: 340°	
	Vertical rotation range: -30° ~ +90°	
	Panning speed range – approx. from 2°/s to 100°/s	
	Tilt speed range – approx. from 2°/s to 69°/s	
	Must support image rotation vertically and horizontally	
	Interfaces:	
	Video interface: 1* HDMI out v.1.3	
	Video interface: 3G-SDI via BNC type connector, 800mVp-p, 750hm	
	Ethernet interface: 1xRJ45: 10M/100M, with VISCA over IP protocol	
	communication function	
	Audio interface: 1* 3.5mm audio jack in, 3.5mm audio jack out	
	USB interface :1xUSB3.0: Type A female	
	Communication interfaces:	
	1xRS232 in: 8pin Min DIN, communication distance: up to approx. 30m, Protocol:	
	VISCA/Pelco-D/Pelco-P	
	1xRS232 out: 8pin Min DIN, communication distance: up to approx. 30m,	
	Protocol: VISCA/Pelco-D/Pelco-P	
	1xRS485: Phoenix type port, communication distance: up to approx. 1200m,	
	Protocol: VISCA	
	Protocols: VISCA/Pelco-D/Pelco-P, TCP/IP, HTTP, RTSP, RTMP, Onvif, DHCP,	
	Multicast	
	Warranty: min. 36 months	
15	USB cable	
	Active optical USB 3.0 cable min. 20m, A male to A male (compatible with the	1
	conference camera, to be connected to the computer)	
16	Recorder for video conference camera	
	Designed to record and broadcast the progress of audio-video conferences	1
	Interfaces: min.1 frontal LCD screen (min.2"), min. 5x HDMI in, min. 4x HDMI	
	out, min. 2 × RS485 (phoenix), min.2 × RS232 (phoenix), min.2 × USB2.0, min.1 ×	
	USB3.0, min.1 $\times$ USB-OTG, min.1 $\times$ Headphone jack of 3.5mm for monitoring,	
	min.2 $\times$ AUDIO LINE IN, min.2 $\times$ AUDIO LINE OUT, min.1 $\times$ RJ45 for Ethernet	
	Disk space: min 1 TB, support extension	
	Operating system: Linux	
	Input Resolution: up to min.4K	
	Output Resolution: up to min.4K	
	Video encoding: H.264, H.265	

Item	Minimal Technical Specifications	Quantity
	Recording format: mp4	
	Possibility to broadcast the audio-video stream in real time on online platforms	
	(the institution's page, YouTube, Facebook, etc.)	
	Chassis type: rackmount max.1U	
17	Warranty: min. 36 months	
17	Video conference AV bridge  Auto-tracking camera controller, with built-in 6*1 matrix switcher to process	1
	different signals, it must manage several cameras at the same time. bridging any	1
	HD, HDMI and audio source through USB into video conferencing applications	
	such as Skype for Business, Zoom, Microsoft Teams.	
	Ports: min. 2x HDMI in, 2x HDMI out, min. 4x3G-SDI in, min. 2xRCA audio in, min.	
	1xUSB2.0, min. 1* RS232 in, min. 1* RS232 out, min. 1* RJ45	
	Input Resolution: 1920 * 1080i @ 60/50 fps, 1920 * 1080p @ 30/25 fps, 1920 *	
	1080p @ 60/50 fps, 1024 * 768p @ 60 fps, 1280 * 0 fps / 70 fps	
	Output Resolution: 1920 * 1080p @ 60Hz	
	Minimum warranty: 36 months	
18	HDMI matrix	
	Modular seamless HDMI matrix incl.:	1
	* 2U rackmount main chassis (1pcs)	
	Control interfaces: min. 1* RJ45, min. 2* RS232	
	* HDMI input modules (2pcs)	
	Resolution: min 1920*1200@60Hz per input Input per module: min. 4 HDMI-A v1.3, min. 4 * 3.5mm audio jack	
	Outputs: min. 4 * 3.5mm audio jack	
	Impedance: min. 50 Ohms	
	4. HDMI output modules (2pcs)	
	Resolution: min 1920*1200@60Hz	
	Outputs per module: min. 4 HDMI-A v1.3, min. 4 * 3.5mm audio jack	
	Impedance: min. 50 Ohms	
	Minimum warranty: 36 months	
19	Cable HDMI to HDMI (type 1)	
	Optical HDMI cable 4K min. 30m (male-male)	1
20	Cable HDMI to HDMI (type 2)	
	Optical HDMI cable 4K min. 20m (male-male)	5
21	Cable HDMI to HDMI (type 3)	
	Optical HDMI cable 4K min. 10m (male-male)	1
22	Power over Ethernet (PoE) Switch	
	Uplink – min. 2 ports @ 10/100 Mbps	1
	Other ports – min. 8 PoE ports @ 10/100 Mbps, 15.4 W (IEEE 802.3af) / 30 W	
	(IEEE 802.3at) per port	
	Max total power of all ports (at least.) - 150 W POE standards – at least IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3af,	
	IEEE802.3at	
	Packet Forwarding Rate – min. 1.45 Mbps	
	Transmission distance, up to 250 m (Cat 6)	
	Transmission distance, up to 250 m (cat o)	

Item	Minimal Technical Specifications	Quantity
	Power supply - AC110-260V input 52V2.88A output	
	Max consumption – not more than 150 W	
	Minimum warranty: 24 months	
23	Interactive display	
	All-in-one touchscreen display:	1
	• recognize at least 40 touch points;	
	• touch recognition accuracy - no higher than 1mm, touch response time - no more than 5ms;	
	Equipped with a microcomputer with a processor composed of at least 8 cores (4	
	Cortex A73 cores and 4 Cortex A53 cores) with Mali G52 graphics chip (4K UHD)	
	or better, RAM min. 8GB, ROM min. 64GB, OS min. Android 13.0 pre-installed from the factory, with:	
	<ul> <li>wireless content sharing software to allow the connection of up to 64 devices simultaneously;</li> </ul>	
	wireless content display software that allows the simultaneous display of	
	information from at least 6 devices (split-screen);	
	• text overwriting tool to write over any image, site, application and to save and	
	share notes;	
	• the possibility to customize the start page by adding, removing and rearranging	
	application icons (shortcut);	
	• sharing content using QR code;	
	• the update of the operating system through the OTA should be automatic and	
	free;	
	Minimum requirements:	
	• Diagonal min. 75", aspect 16:9	
	Display technology: VA-ADS with Direct-LED backlight	
	Physical dimensions: max. 1743 x 1032 mm	
	• Pixel pitch (max.): 0.43 x 0.43 mm	
	Native resolution: 3840 x 2160 pixels - 4K Ultra High Definition     Trypical brightness and less than 400 add/se2	
	• Typical brightness: not less than 400 cd/m <sup>2</sup>	
	<ul> <li>Maximum brightness: not less than 450 cd/m²</li> <li>Typical contrast: 1200:1</li> </ul>	
	• Dynamic contrast: 5000:1	
	• Viewing angle: 178° / 178°	
	• Colors: 1.07 billion colors (10 bit)	
	• Image response time (typ.): no higher than 8 ms	
	• Refresh rate: 60 Hz (@ UHD)	
	• Estimated lifetime of the device screen: 50,000 hours	
	• incorporates an amplifier and at least 2 loudspeakers of at least 20W each and	
	a subwoofer of at least 20W;	
	• to be equipped with protective glass with a thickness of max. 2.7mm (hardness	
	level no less than MOHS 8, with scratch resistance) glued over the display using	
	"optical bonding" technology (without air space); the protective glass must be	
	anti-glare, anti-reflection, anti-aging and anti-static, or better performance;	

Item	Minimal Technical Specifications	Quantity
	• to be equipped with at least one motion detection sensor to optimize	•
	electricity consumption by automatically disconnecting the monitor in case it is	
	not used and there is no activity in the room for a certain period of time;	
	• to be equipped with at least one ambient light detection sensor for the	
	automatic adaptation of the image brightness;	
	• to be equipped with at least one programmable physical button (to which a quick command can be assigned) to make the access time to the most frequently used function more efficient;	
	• to support the mode of displaying 2 applications in split-screen mode.  Connectivity (minimum)	
	• Inputs: 2x HDMI 2.0 (with CEC and ARC functionality), 1x USB 3.0 type-C (with	
	up to 100W connected laptop power supply, which can transmit audio, video,	
	touch data and all peripherals connected to the display (example: webcam,	
	microphone etc)), 1x USB 3.0 type-C (to transmit audio, video, touch data and all	
	peripherals connected to the display (example: webcam, microphone etc)), 1x	
	DisplayPort 1.2, 1x USB 3.2 type A (for Android), 2x USB 3.2 type A (dynamic), 3x USB 3.0 (touch)	
	• AV outputs: 1x HDMI 2.0, 1x S/PDIF Optical audio, 1x 3.5mm audio jack	
	• Control: 1x RS232	
	• LAN: 2x RJ45 (1000Mbps)	
	• Wi-Fi: min. WiFi 6 (802.11ax) with hotspot (2.4Ghz and 5Ghz)	
	Slot for optional OPS module	
	Maximum weight: 52kg	
	• Energy consumption – max. 151 Watt	
	Accessories included in the set:	
	User Manual, 1x IR Remote Control, 1x Power Cable, 1x HDMI Cable min. 3m, 1x	
	USB type-C cable min. 3m, 1x USB cable min. 3m (touch), min. 4x passive pencils	
	(3 stylus and 1 marker) with magnetic fixation on the lower front side of the	
	display.	
	Minimum warranty: 60 months	
24	Open Pluggable Specification (OPS) module	
	Compatible with interactive display.	1
	Form factor: OPS. CPU base frequency min 2.4 GHz, turbo frequency min 4.2	
	GHz, release year min 2020, min 4 cores, min. 8 threads, min. 8 MB cache,	
	RAM min. 16 Gb DDR4, SSD min. 256Gb SATA M.2, WiFi 6E (802.11ax), Bluetooth	
	min. 5.3,	
	min. 2*USB3.1 Type-A, min. 2*USB2.0 Type-A, min. 1*USB 3.1 Type-C, min.	
	1*HDMI 2.0 in, Windows 11 Pro license	
	Minimum warranty: 36 months	
25	LED TV	
	55" diagonal, 3840x2160 4K UHD, HDR10, 120 Hz refresh rate	2
	Panel type: OLED, Smart Remote Control, Android TV OS, GPU Mali-G52, Internal	_
	storage min. 16 GB, CPU min. 4x Cores, Wi-Fi: Wi-Fi 802.11 a/b/g/n/ac, Built-in	
	speakers: 3x 10 W, 2x USB Type-A, VESA 300x300	
	Minimum warranty: 36 months	
	The state of the s	

Item	Minimal Technical Specifications	Quantity
26	TV wall mount	
	Tilting 5° / -15°, swiveling 60° / -60°, wall distance 53mm up to 464mm, load	2
	capacity up to 40kg, max. VESA 400x400.	
	Made of steel, with cable management	
	Minimum warranty: 24 months	
27	AiO (All-in-One) computer <sup>1</sup>	
	Form factor: All-in-One computer. Display: min. 27" diagonal, FHD, IPS	1
	CPU max. frequency at least 4.4 GHz, release year min 2022, min 8 cores, min. 8	
	threads, min. 8 cores, min. 12 MB cache, RAM min. 16 Gb DDR4, SSD min. 256Gb	
	SATA M.2, 2.5" HDD min. 1Tb @ 5400rpm, WiFi 5 (802.11ac), Bluetooth min. 5.1,	
	integrated webcam 5Mpx, min. 2*USB3.2 Type-A, min. 2*USB2.0 Type-A, min.	
	1*RJ45 @ 1Gbps, min. 1*HDMI 2.0 out, USB Keyboard, USB mouse, Windows 11	
	Pro x64 license	
	Minimum warranty: 36 months	
28	Materials and accessories	
	Rack 15U, materials, cables and other accessories needed to connect, setup and	1
	commissioning the system must be provided by the bidder	
29	Surge Protector	
	Length: 5 m, 5 sockets	5
30	Transportation and installation services	
	Transportation and Installation services, routing, setup and commissioning	1
	services.	
	<b>NB:</b> to be noted that the system setup must include a PC software to allow to	
	start/pause/stop the streaming and the audio-video signal registration.	
	Address: Superior Council of Magistracy. Address: 5, M. Eminescu street, Chisinau city	

# Lot 2 – Server/NAS and UPS equipment

Minimal Technical Specifications	Quantity
Network Attached Storage (NAS)	
The computing node must meet the following requirements:  • Have a form factor for installation in a standard server rack and have a height of no more than 2U;  • Chassis configuration – 12 3.5" SATA/SAS drives;  • Have a set of telescopic rails for installing the computing node in the rack;  • Have a set of cables for connecting to the power supply;  • Have a key-lockable front panel that restricts access to hard drives, with an LCD display showing the status of the server, allowing the initial configuration of the	1
- ( ( ( ( ( ( ( ( ( ( ( ( ( ( ( ( ( ( (	Network Attached Storage (NAS)  The computing node must meet the following requirements:  Have a form factor for installation in a standard server rack and have a height of no more than 2U;  Chassis configuration – 12 3.5" SATA/SAS drives;  Have a set of telescopic rails for installing the computing node in the rack;  Have a set of cables for connecting to the power supply;  Have a key-lockable front panel that restricts access to hard drives, with an LCD

<sup>&</sup>lt;sup>1</sup> **Important Notice:** The computer manufacturer must have received 50 or a higher reliability score according to the Rescuecom 2020 Computer Reliability Report, available at <a href="https://www.prnewswire.com/news-releases/2020-rescuecom-computer-reliability-report-301068125.html">https://www.prnewswire.com/news-releases/2020-rescuecom-computer-reliability-report-301068125.html</a>. Offers failing to respect this requirement will not be considered.

Item	Minimal Technical Specifications	Quantity
	• Have a module with 2 (two) M.2 solid-state drives with a volume of at least 480	
	GB each installed inside the module housing and supporting operation in	
	hardware RAID-1 mode, and supporting the installation of an OS or hypervisor	
	on them, and booting from them;	
	• There must be a receiver-transmitter with a wireless data transmission module	
	that provides access to the server from smartphones and any mobile devices to	
	receive server configuration data and server diagnostics;	
	Must have a housing opening sensor with the ability to set up remote	
	notification of this event;	
	Have a processor with at least 8 cores operating at a frequency of at least 1.8	
	GHz, support memory operation at a frequency of at least 4000 MHz, and have a	
	cache memory of at least 22 MB. The maximum power dissipation of the	
	processor should be no more than 125 watts.	
	Must support the installation of up to 16 memory modules operating at a	
	frequency of at least 4000 MHz;	
	At least 2 RDIMM memory modules with a capacity of at least 16 GB each	
	operating at a frequency of at least 4800 MHz must be installed;	
	• At least 8 NL-SAS disks with a volume of at least 8TB must be installed;	
	• A RAID controller with at least the same characteristics must be installed:	
	- RAID levels: 0, 1, 5, 6, 10, 50, 60;	
	- Pass-through/Non-RAID mode;	
	- NV cache 8GB DDR4;	
	- Disk support: 3 Gbps SATA, 6 Gbps SATA/SAS and 12 Gbps SAS;	
	Have at least 1 OCP NIC 3.0 network adapter with at least 4 1GbE ports, as well	
	as 2 1GbE LOM ports. The network adapter should not occupy slots designed for	
	installing additional PCle adapters;	
	Have a dedicated 1 GbE network port to connect to the server management	
	and monitoring controller;	
	Must support the optional installation of at least 2 microSD cards inside the	
	server, with hardware RAID 1 for fault-tolerant booting and operation of the	
	hypervisor; • Have at least 3 (three) USB ports (1 USB 2.0 on the front panel, 1 USB 3.0 and 1	
	USB 2.0 on the back of the server);	
	Have at least 1 (one) micro-USB port on the front panel for direct connection	
	to the server management and monitoring controller;	
	Must have a Trusted Platform Module 2.0	
	cryptoprocessor • Must have at least two Platinum power supplies with a	
	capacity of at least 800 watts each, hot-swappable; support for power	
	redundancy;	
	Availability of a set of telescopic rails with a cable organizer for installation in a	
	rack;	
	Must be compatible with at least the following operating systems and	
	hypervisors:	
	- Microsoft Windows Server 2019, 2022;	
	- Red Hat Enterprise Linux 7.9, 8.2, 8.3;	
	- VMware ESXi 6.7 U3, 7.0 U1, 7.0 U2;	
	- Ubuntu 20.04;	
	· · · · · · · · · · · · · · · · · · ·	

Item	Minimal Technical Specifications	Quantity
	- Citrix XenServer 8.2 LTSR;	
	- Novell SuSE Linux Enterprise Server 15 SP2.	
	<ul> <li>Must have built-in hardware and software for remote management and</li> </ul>	
	monitoring, providing the following functions:	
	- Remote access to the management console of the computing node via web	
	browsers, command-line interface over ssh and telnet protocols, IPMI and Redfish;	
	- Automatically informing the administrator about all failures and predictions of malfunction of the disk subsystem, memory modules, power supplies, fans and processors by e-mail or by displaying a message to the administrator console;	
	- Displaying inventory information about installed components of the computing	
	node, including information about installed versions of microcode server components, information about MAC addresses and WWN network controllers	
	and FC adapters, including virtual ones;	
	- Remote reboot, switching on/off the computing node (including booting from a virtual optical disk);	
	- Remote interception of the computing node management console (virtual console): the screen, keyboard, and coordinate-graphic pointer both at the stage	
	of loading the computing node and during operation of operating systems. The	
	virtual console should be able to manage the power supply of the computing	
	node, the ability to specify a boot device, with simultaneous connection of up to	
	6 users and interaction in messaging mode. The virtual console must support	
	using a web browser and the HTML5 standard, without the need to use Java and ActiveX plugins.;	
	- The ability to collect information about the utilization level of the CPU and RAM of the server without the need to install agent software in the OS;	
	- The ability to control RAID controllers installed inside the computing node	
	enclosure via the web interface or the command interface of the control module without the need to install agent software in the OS. At a minimum, it should be	
	possible to:	
	The ability to control the RAID controller without having to reboot the	
	computing node;	
	<ul> <li>Monitoring the status of drives connected to the RAID controller, including NVMe drives;</li> </ul>	
	Monitoring the status of virtual disks;	
	Creating, deleting and configuring virtual disks;	
	Changing RAID controller settings;	
	• Expanding the capacity of virtual disks without interrupting access to them;	
	Changing the RAID level of virtual disks without interrupting access to them;	
	- The ability to record the configuration of the computing node, drivers, and	
	store a backup image of the computing node for rebooting in case of problems	
	on non-volatile media installed inside the computing node enclosure or on a	
	network file resource;	
	- The ability to save a screenshot of the system failure description screen with	
	diagnostic information output;	
	- The ability to export diagnostic information about the status of the computing	
	node, including logs from both the server management module and logs of the	

Item	Minimal Technical Specifications	Quantity
	operating system or hypervisor, in a single consolidated report via the web	
	interface or command-line interface.	
	- The ability to use hardware and software tools to prepare for the installation of	
	the operating system (configuring volumes, creating partitions, copying drivers,	
	creating response files for OS installers) that do not require the use of external	
	media;	
	- The possibility of applying microcode updates to the components of the	
	computing node both through the interface of the server management module	
	and from supported operating systems;	
	- The server management module must have the functionality to securely verify	
	the integrity and immutability of the microcode update packages of the	
	computing node component at the stage of preparing the update;	
	Availability of a full set of Windows Server 2022 Standard licenses for licensing      This course.	
	this server;	
2	Must be supplied with support for at least 3 years.  Uninterruptible Power Supply (UPS)	
	Online Double Conversion UPS with automatic static bypass and power factor	1
	correction system included for advanced protection of critical equipment:	1
	- Power Rating: 5kVA/4.5kW;	
	- Power factor: 0.91;	
	- Input voltage: 176-276V without derating; 100V-276V with maximum 40%	
	Load;	
	- Input frequency range: 40-70 Hz	
	- Output voltage: 230V standard - (200/208/220/230/240V selectable);	
	- Output frequency: 50/60Hz with auto-selection depending on the power supply	
	network;	
	- Input connections: Terminal block (up to 10mm2)	
	- Output connectors: terminal block + 2 controlled socket groups of 4 IEC C13(10	
	A) and 2 IEC C19 (16A)	
	- User interface: Graphical LCD screen with access to information on various	
	parameters, including power consumption, alarms and local configuration	
	possibilities, 4 LEDs for notice / alarms;	
	- Management ports: USB (1,8 meters length USB cable Included), RS232 (1,8	
	Meters Length serial cable Included), Terminal block for Remote Power Off	
	(remote shutdown in case of emergency), Terminal block for Remote Off/On	
	(remote closing/opening), Output relay for various alarms;	
	Remote Management Card:	
	- Network card available for remote monitoring and control of UPS status via	
	Fast Ethernet 10/100/1000BaseT,	
	- Protocols: HTTP, HTTPS 1.1, TLS 1.2, SNMP V1, SNMP V3, NTP, SMTP, SMTPS	
	BOOTP/DHCP, CLI, SSH, ARP;	
	- Operating Temperature: 0-40 grade Celsius;	
	- Cyber Security Certificate (IEC 62443-2 and UL 2009-2-1)	
	• Batteries:	
	- quick battery replacement possibility without shutting down the UPS	
	(HotSwap);	

Item	Minimal Technical Specifications	Quantity				
	- Advanced battery management system to extend battery life and float					
	temperature compensation;					
	- Automatic battery testing, deep discharge protection;					
	- Battery runtime: 10 minutes at 3,15kW load / 13 minutes at 2,25kW load (with					
	the possibility of extending the autonomy with compatible external battery					
	modules and automatic battery detection);					
	Accessories: the possibility of adding, if necessary, an external maintenance					
	bypass of 6kVA max. compatible with the product, both technically and					
	physically;					
	- Form factor: rackmount, maxim 3U with all necessary accessories included					
	(Tower convertible when needed)					
	- Audible Noise: 50dB					
	• Standards:					
	- Safety: IEC/EN 62040-1, UL 1778, CSA 22.2;					
	- Electromagnetic compatibility: IEC/EN 62040 -2, FCC Class A, IEC/EN 62040-3;					
	- Approvals: CE /CB report (TUV) / Energy Star/ UL					
	- Standard warranty: 2 years for electronics / 2 years for batteries – expandable.					
3	Transportation and installation services					
	Address: Superior Council of Magistracy. Address: 5, M. Eminescu street, Chisinau city	1				

Offerors are required to submit their quotations by using the template provided in the "Annex 3: Quotation Submission Form".

# **REQUIREMENTS**

All services offered in response to this RFQ or supplied under any resulting award must meet **USAID Geographic Code 935** in accordance with the United States Code of Federal Regulations (CFR), 22 CFR §228. The cooperating country for this RFQ is Republic of Moldova.

Offerors may not offer or supply services or any commodities that are manufactured or assembled in, shipped from, transported through, or otherwise involving any of the following countries: Cuba, Iran, North Korea, Syria.

Any and all items that are made by Huawei Technology Company, ZTE Corporation, Hytera Communications Corporation, Hangzhou Hikvision Digital Technology Company, Dahua Technology Company will not be accepted. If quotes include items from these entities, please note that they will be deemed not technically responsive and excluded from competition.

By submitting an offer in response to this RFQ, the offeror certifies that it and its principal officers are not debarred, suspended, or otherwise considered ineligible for an award by the U.S. Government. Dexis will not award a contract to any firm that is debarred, suspended, or considered to be ineligible by the U.S. Government.

All responses must be in English. Offerors must submit the following in order to be considered responsive and eligible for award:

- 1. A contact name, email address, and telephone number to facilitate communication between Dexis and the prospective contractor.
- 2. General information about the contractor's history and experience.
- Copy of offeror's registration documents: Extract (Extras din Registrul de stat al persoanelor juridice). Prospective contractor must be legally registered under the laws of the Republic of Moldova.
- 4. **Statement of satisfactory performance** (Certificates/ Letters) from the top three (3) clients in terms of Contract value in similar field.
- 5. Evidence of Responsibility (Annex 1)\*
- 6. Section 889 Statement for Subcontractors and Vendors (Annex 2)\*
- 7. **Quotation Submission Form** (Annex 3)\*, including technical specifications for the proposed equipment.
- 8. Unique Entity Identifier (UEI), if applicable. Companies or organizations, whether for-profit or non-profit, shall be requested to provide a Unique Entity Identifier (UEI) number if selected to receive an award in response to this RFQ valued greater than or equal to USD\$30,000 (or equivalent in other currency). If the Offeror does not have a UEI number and is unable to obtain one before the submission deadline, Offeror shall include a statement noting their intention to obtain a UEI number should it be selected as the successful offeror or explaining why registration for a UEI number is not possible. Contact sam.gov to obtain a number. Further guidance on obtaining a UEI number is available from Dexis upon request. By submitting this quotation, the offeror agrees to comply with this requirement as applicable if selected.
- 9. **Subcontractor/Vendor UEI and Executive Compensation Self-Certification,** if applicable. This form shall be completed only if the value is over \$30,000 and will be required before the agreement signature. By submitting this quotation, the offeror agrees to comply with this requirement as applicable if selected.
- 10. **Vendor Source and Nationality Statement,** if applicable. For all procurements of commodities at or above \$25,000 under USAID-funded contracts, vendors must complete and sign the statement before the agreement signature.
- 11. If a government, its agents, or agencies, have an ownership or managerial interest in the company, the prospective contractor must indicate this when submitting its offer. Failure to do so will result in the prospective contractor's offer being removed from consideration.
- 12. The Offeror must agree to keep the bid valid for a minimum of 60 calendar days. The prices must be valid for the entire duration of the contract.
- 13. The equipment and software presented in the quotation must be available for delivery and installation within 6 (six) months upon contract signature.

\*All the Annexes (1-3) must be dully completed and signed and submitted as separate documents.

#### **EVALUATION**

All Responses must contain the elements outlined in this RFQ for Dexis to comprehensively evaluate each quotation.

Dexis will first evaluate quotations for compliance with the mandatory requirements/ elements of this RFQ. Quotations that do not contain all mandatory requirements/ elements may not be considered.

Offerors are responsible for ensuring that their offers are received by Dexis in accordance with the instructions, terms, and conditions described in this RFQ. Failure to adhere with instructions described in this RFQ may lead to disqualification of an offer from consideration.

Offerors applying will be evaluated based on the minimum technical requirements below:

- Officially registered legal entity with full capacity to act under the laws of the Republic of Moldova and possess all licenses, permits and government approvals necessary for performance of the work.
- Minimum 5-year of successful work experience in selling and distribution of IT equipment and software on the Moldovan market;
- Statement of satisfactory performance (Certificates/ Letters) from the top three (3) clients in terms of Contract value in similar field;

The agreement(s) will be awarded to the lowest price technically compliant offer(s).

**Partial Quotes:** are allowed.

Dexis reserves the right to accept all or part of the quotation when awarding the contract. While preference will be given to offerors who can address the full technical requirements of this RFQ, Dexis may issue a partial award or split the award among various suppliers, if in the best interest of the Model Court Initiative Project.

#### SCHEDULE OF EVENTS

Release of RFQ April 8, 2024

Questions Due April 12, 2024, 17:00 local time

Answers from Dexis April 15, 2024

RFQ Closes – Responses Due April 18, 2024, 17:00 local time

Estimated Date of Award May 8, 2024

The schedule noted above may be changed at any time in the sole discretion of Dexis. All communication must adhere to this schedule and shall be to the attention of <a href="mailto:asoltan@dexisonline.com">asoltan@dexisonline.com</a> and <a href="mailto:mgrosu@dexisonline.com">mgrosu@dexisonline.com</a>.

All questions or clarifications regarding this RFQ must be in writing and submitted to the attention of <a href="mailto:asoltan@dexisonline.com">asoltan@dexisonline.com</a> and <a href="mailto:mgrosu@dexisonline.com">mgrosu@dexisonline.com</a>. RFQ process and subsequent evaluation. Any

answers received outside the official channel, whether received verbally or in writing, from employees or representatives of Dexis, will not be considered official responses regarding this RFQ.

#### **SUBMISSION INSTRUCTIONS**

Bids must be received via email by **April 18, 2024, and 17:00 local time**. Offerors should send their bids by email to the individuals identified above (10 MB limit per email).

Offers must be on the company letterhead with the company's contact name and address. The subject line of the offer transmission email must identify the RFQ reference number (2003-RFQ-2024/0005) and the Offeror's name.

#### **GENERAL TERMS AND CONDITIONS**

- Collusion is strictly prohibited. Collusion is defined as an agreement or compact, written or oral, between two or more parties with the goal of limiting fair and open competition by deceiving, misleading, or defrauding a third party.
- 2. Prices quoted must be valid for the entire length of the contract.
- 3. Unit prices are required and in the case of discrepancies between unit price and total price, the unit price will be taken as reference basis in the evaluation.
- 4. All procurements will be subject to Dexis contractual terms and conditions, contingent on the availability of client funding.
- 5. Dexis reserves the right to accept or reject any quotation or stop the procurement process at any time, without assigning any reason or liability.
- 6. Dexis reserves the right to accept all or part of the quotation when awarding the contract.
- 7. All information provided by Dexis in this RFQ is subject to change at any time. Dexis makes no certification as to the accuracy of any item and is not responsible for or liable for any reliance on or use of the information or for any claims asserted therefrom.
- 8. Dexis reserves the right to require any prospective contractor to enter into a non-disclosure agreement.
- 9. The RFQ does not oblige Dexis to pay for any costs, of any kind whatsoever, which may be incurred by the prospective contractor or any third parties, in connection with the Response. All Responses and supporting documentation shall become the property of Dexis.
- 10. The award is subject to Dexis's standard terms and conditions. Please note that Dexis' standard payment terms are ten (10) net banking days upon receipt of the complete documentation after acceptance of the deliverables. No advance payments are possible.

Dexis has zero tolerance for fraud. Fraud is any act or omission that intentionally misleads, or attempts to mislead, to obtain a benefit or to avoid an obligation. If you have concerns about potential fraud in any way related to Dexis projects, contracts, or activities, please visit <a href="https://www.lighthouse-services.com/index.html">https://www.lighthouse-services.com/index.html</a>.

#### Company Name

Company Name makes the following statements with respect to Contractor Responsibility:

- 1) *Company Name* has adequate financial resources to perform the contract, or the ability to obtain them;
- 2) *Company Name* is able to comply with the required or proposed delivery or performance schedule, taking into consideration all existing commercial and governmental commitments;
- 3) Company Name has a satisfactory performance record;
- 4) Company Name has a satisfactory record of integrity and business ethics;
- 5) Company Name has the necessary organization, experience, accounting and operational controls, and technical skills, or the ability to obtain them (including, as appropriate, such elements as production control procedures, property control systems, quality assurance measures, and safety programs applicable to materials to be produced or services to be performed by the prospective contractor and subcontractors).;
- 6) *Company Name* has the necessary production, construction, and technical equipment and facilities, or the ability to obtain them; and
- 7) Company Name is qualified and eligible to receive an award under applicable laws and regulations (e.g., Equal Opportunity, Clean Air and Water, Small Business Subcontracting, etc.)

I declare under penalty of perjury that the foregoing is true and correct.

Name

Title, Company Name

# Annex 2: Prohibition on Contracting for Certain Telecommunications and Video Surveillance Services or Equipment Disclosure

Off	fferor Name:	("Offeror")					
	s used in this document, "Prohibited telecommur quipment" means:	ications and Video Surveillance Services or					
	any subsidiary or affiliate of such entities);	uawei Technologies Company or ZTE Corporation (or					
(2)	critical infrastructure, and other national securi telecommunications equipment produced by H Hikvision Digital Technology Company, or Dahu						
(3)	of such entities); (3) Telecommunications or video surveillance services provided by such entities or using such						
(4)	equipment; or  4) Telecommunications or video surveillance equipment or services produced or provided by an entity that the U.S. Secretary of Defense, in consultation with the U.S. Director of National Intelligence or the U.S. Director of the Federal Bureau of Investigation, reasonably believes to be an entity owned or controlled by, or otherwise connected to, the government of a covered foreign country.						
	ease select "will" or "will not" regarding Offeror rveillance services or equipment:	s use of prohibited telecommunications and video					
	fferor [ ] will [ ] will not incorporate any prohibit ervices or equipment in any equipment or services						
ans	you answered "will" to the question above, you newered "will not" to the question above, you are allow and can skip to the signature block.	nust complete the following information. If you exempt from providing the information requested					
Sι	For prohibited telecommunications and video surveillance <b>equipment</b> , please provide the following information:						
	<ul> <li>The entity that produced the prohibited telecommunications equipment (include entity name, unique entity identifier, CAG code (which can be found <a href="here">here</a>), and whether the entity was the original equipment manufacturer (OEM) or a distributor, if known)</li> </ul>	E					

<ul> <li>A description of all prohibited telecommunications equipment offered (include brand; model number, such as OEM number, manufacturer part number, or wholesaler number; and item description, as applicable)</li> <li>Explanation of the proposed use of prohibited telecommunications equipment and any factors relevant to determining if such use would be permissible under the</li> </ul>	
prohibition in paragraph (b)(2) of this provision	
For prohibited telecommunications and video surveillance services, please provide the following information:	
If the service is related to item maintenance: a description of all prohibited telecommunications services offered (include on the item being maintained: Brand; model number, such as original equipment manufacturer (OEM) number, manufacturer part number, or wholesaler number; and item description, as applicable); or	
<ul> <li>If not associated with maintenance, the Product Service Code ("PSC") of the service being provided (which can be found <a href="here">here</a>); and explanation of the proposed use of prohibited telecommunications services</li> </ul>	

By the signature of Offeror's authorized representative below, Offeror certifies that the foregoing information is true and accurate as of the date of execution of this reporting statement.

Dated:	Ву:
	Name:
	Title:

# **ANNEX 3: QUOTATION SUBMISSION FORM**

Bidders are requested to complete this form, sign it and return it as part of their quotation along with the technical specifications for the proposed equipment. The bidder shall fill in this form in accordance with the instructions indicated. No alterations to its format shall be permitted and no substitutions shall be accepted.

The prices must be provided for the Lot(s) you have chosen to submit an offer.

# <u>Lot 1 – Videoconferencing equipment</u>

2 Chairman unit  Insert proposed technical specifications 1 Yes  \( \text{No} \)  3 Delegate unit (Type 1)  Insert proposed technical specifications 11 Yes  \( \text{No} \)  4 Delegate unit (Type 2)  Insert proposed technical specifications 2 Yes  \( \text{No} \)  5 Delegate unit (Type 3)  Insert proposed technical specifications 3 Yes  \( \text{No} \)  6 Software module for voting procedure  Insert proposed technical specifications 1 Yes  \( \text{Yes} \)	Details (include details if any deviations)
3 Delegate unit (Type 1)  Insert proposed technical specifications  11 Yes  No  4 Delegate unit (Type 2)  Insert proposed technical specifications  2 Yes  No  5 Delegate unit (Type 3)  Insert proposed technical specifications  3 Yes  No  6 Software module for voting procedure	
Insert proposed technical specifications  4 Delegate unit (Type 2)  Insert proposed technical specifications  2 Yes □ No □  5 Delegate unit (Type 3)  Insert proposed technical specifications  3 Yes □ No □  6 Software module for voting procedure	
4 Delegate unit (Type 2)  Insert proposed technical specifications  5 Delegate unit (Type 3)  Insert proposed technical specifications  3 Yes □ No □  6 Software module for voting procedure	
4 Delegate unit (Type 2)  Insert proposed technical specifications 2 Yes \( \text{No} \)  5 Delegate unit (Type 3)  Insert proposed technical specifications 3 Yes \( \text{No} \)  6 Software module for voting procedure	
Insert proposed technical specifications 2 Yes □ No □  5 Delegate unit (Type 3)  Insert proposed technical specifications 3 Yes □ No □  6 Software module for voting procedure	
Software module for voting procedure  No □  No □  No □  No □  No □  Software module for voting procedure	
5 Delegate unit (Type 3)  Insert proposed technical specifications 3 Yes  No  6 Software module for voting procedure	
Insert proposed technical specifications 3 Yes ☐ No ☐  Software module for voting procedure	
No   Software module for voting procedure	T
Insert proposed technical specifications 1	
insert proposed technical specifications	
No □	
7 Software module for integrated circuit (IC) card management	
Insert proposed technical specifications   Yes □	
No □	
8 IC card programming unit	
Insert proposed technical specifications 1	
No 🗆	
9 Sound Amplifier  Insert proposed technical specifications 1 Yes	
Insert proposed technical specifications   1   Yes □   No □	
10 Speaker	
Insert proposed technical specifications 4 Yes	
No 🗆	

			Unit	TOTAL		<b>-</b> . <b>1</b> . /:
Item	Minimal Technical Specifications	Quantity	price MDL, VAT 0%	price MDL, VAT 0%	Is Bid compliant?	<b>Details</b> (include details if any deviations)
11	Wireless microphone system					
	Insert proposed technical specifications	1			Yes □	
12	Foodback suppressor				No □	
12	Feedback suppressor  Insert proposed technical specifications	1			V 🗆	
	insert proposed technical specifications	1			Yes □	
12	Digital signal processor (DCD)				No □	
13	Digital signal processor (DSP)	1		<u> </u>	V 🗆	
	Insert proposed technical specifications	1			Yes □	
	0 1				No □	
14	Conference camera					
	Insert proposed technical specifications	4			Yes □	
					No □	
15	USB cable					
	Insert proposed technical specifications	1			Yes □	
					No □	
16	Recorder for video conference camera				T.	
	Insert proposed technical specifications	1			Yes □	
					No □	
17	Video conference AV bridge		T	Г	ı	
	Insert proposed technical specifications	1			Yes □ No □	
18	HDMI matrix				L	
	Insert proposed technical specifications	1			Yes □	
					No □	
19	Cable HDMI to HDMI (Type 1)					
	Insert proposed technical specifications	1			Yes □	
					No □	
20	Cable HDMI to HDMI (Type 2)				_	
	Insert proposed technical specifications	5			Yes □	
					No □	
21	Cable HDMI to HDMI (Type 3)				L	
	Insert proposed technical specifications	1			Yes □	
					No □	
22	Power over Ethernet (PoE) Switch					
	Insert proposed technical specifications	1			Yes □	
	, ,				No □	
23	Interactive display				,	
	Insert proposed technical specifications	1			Yes □	
	, ,	_			No □	
24	Open Pluggable Specification (OPS) mod	dule			.,,,,	
	Insert proposed technical specifications	1			Yes □	
				<u> </u>	163 🗀	

Item	Minimal Technical Specifications	Quantity	Unit price MDL, VAT 0%	TOTAL price MDL, VAT 0%	Is Bid compliant?	<b>Details</b> (include details if any deviations)
					No □	
25	LED TV					
	Insert proposed technical specifications	2			Yes □	
					No □	
26	TV wall mount					
	Insert proposed technical specifications	2			Yes □	
					No □	
27	AiO (All-in-One) computer <sup>2</sup>					
	Insert proposed technical specifications	1			Yes □	
					No □	
28	Materials and accessories					
	Insert proposed technical specifications	1			Yes □	
					No □	
29	Surge Protector					
	Insert proposed technical specifications	5			Yes □	
					No □	
30	Transportation and installation services					
	Address: Superior Council of	1			Yes □	
	Magistracy. Address: 5, M. Eminescu				No □	
	street, Chisinau city			<u> </u>		
				Total, M	IDL (VAT 0%):	

# Lot 2 - Server/NAS and UPS equipment

Item	Minimal Technical Specifications	Quantity	Unit price MDL, VAT 0%	TOTAL price MDL, VAT 0%	Is Bid compliant?	<b>Details</b> (include details if any deviations)
1	Network Attached Storage (NAS)					
	Insert proposed technical specifications	1			Yes □	
					No □	
2	Uninterruptible Power Supply (UPS)					
	Insert proposed technical specifications	1			Yes □	
					No □	
3	Transportation and installation services					
	Address: Superior Council of	11			Yes □	
	Magistracy. Address: 5, M. Eminescu street, Chisinau city				No □	

<sup>&</sup>lt;sup>2</sup> Important Notice: The computer manufacturer must have received 50 or a higher reliability score according to the Rescuecom 2020 Computer Reliability Report, available at <a href="https://www.prnewswire.com/news-releases/2020-rescuecom-computer-reliability-report-301068125.html">https://www.prnewswire.com/news-releases/2020-rescuecom-computer-reliability-report-301068125.html</a>. Offers failing to respect this requirement will not be considered.
2003-RFQ-2024/0005
Page 24

Item	Minimal Technical Specifications	Quantity	Unit price MDL, VAT 0%	TOTAL price MDL, VAT 0%	Is Bid compliant?	<b>Details</b> (include details if any deviations)
	Total, MDL (VAT 0%):					

# **Compliance with requirements**

	Your responses						
Requirements	Yes, we will comply	No, we will not comply	If you cannot comply, please indicate counter - offer				
Delivery and Installation time – 180 calendar days							
Validity of Quotation – 60 calendar days							
Payment terms – 10 working days after invoice date, following satisfactory receipt of services							
Company name:		Authorized Signature:					
Address: Phone No.: Email Address:		Name: Title: Date:					